

## Detailed Specifications

|                                    |                                |
|------------------------------------|--------------------------------|
| <b>Frame Width:</b>                | 40[mm]                         |
| <b>Frame Height:</b>               | 40[mm]                         |
| <b>Frame Depth:</b>                | 56[mm]                         |
| <b>Max. Air Flow:</b>              | 30.3[CFM]                      |
| <b>Max. Air Flow:</b>              | 0.86[m3 per min]               |
| <b>Max. Static Pressure:</b>       | 3.1[In H2O]                    |
| <b>Max. Static Pressure:</b>       | 771[Pa]                        |
| <b>Noise:</b>                      | 69[dB]                         |
| <b>Life Expectancy:</b>            | 40 degrees C 70,000 Hours[L10] |
| <b>Bearing Type:</b>               | Ball Bearing                   |
| <b>Speed Control:</b>              | PWM                            |
| <b>Nominal Voltage:</b>            | 12[V]                          |
| <b>Operating Voltage - Lower:</b>  | 10.8[V]                        |
| <b>Operating Voltage - Upper:</b>  | 12.6[V]                        |
| <b>Current:</b>                    | 1.3[A]                         |
| <b>Input Power:</b>                | 15.6[W]                        |
| <b>Mass:</b>                       | 90[g]                          |
| <b>Tach / Locked Rotor Output:</b> | Tach Output                    |
| <b>Status:</b>                     | Active                         |

PWM Speed Control Fans