

## Detailed Specifications

|                                    |                               |
|------------------------------------|-------------------------------|
| <b>Frame Width:</b>                | 80[mm]                        |
| <b>Frame Height:</b>               | 80[mm]                        |
| <b>Frame Depth:</b>                | 25[mm]                        |
| <b>Max. Air Flow:</b>              | 35.5[CFM]                     |
| <b>Max. Air Flow:</b>              | 1[m3 per min]                 |
| <b>Max. Static Pressure:</b>       | 0.13[In H2O]                  |
| <b>Max. Static Pressure:</b>       | 32.3[Pa]                      |
| <b>Fan Speed:</b>                  | 3000[RPM]                     |
| <b>Noise:</b>                      | 31[dB]                        |
| <b>Life Expectancy:</b>            | 25 degree C 50,000 Hours[L10] |
| <b>Bearing Type:</b>               | Ball Bearing                  |
| <b>Nominal Voltage:</b>            | 24[V]                         |
| <b>Operating Voltage - Lower:</b>  | 10[V]                         |
| <b>Operating Voltage - Upper:</b>  | 27.6[V]                       |
| <b>Current:</b>                    | 0.1[A]                        |
| <b>Input Power:</b>                | 2.4[W]                        |
| <b>Mass:</b>                       | 95[g]                         |
| <b>Tach / Locked Rotor Output:</b> | Locked Rotor                  |
| <b>Status:</b>                     | EOL                           |

DC Axial Fans