

General Specifications

Motor Structure: Shaded Pole Induction Motor
Motor Protection: Impedance Protection
Insulation Resistance: 10M Ohm or over with DC500V Megger
Dielectric Withstand Voltage: AC 700V 1s
Allowable Ambient Temperature Range:
-10 degree C ~ +70 degree C (Operating)
-40 degree C ~ +70 degree C (Storage)
(non-condensing environment)

4715TS-23T-B50-AM0 metal pot product picture



4715TS-23T-B50-AM0 metal pot panel cut out



Material

Casing: Aluminum Black Painting
Impeller: Steel
Lead Wire or Terminal: AWG22, UL3266 Faston #110 or equivalent

4715TS-23T-B50-AM0 metal pot characteristics curve



4715TS-23T-B50-AM0 metal pot product drawing



Detailed Specifications

Expected Life:	*Failure rate 10% 25deg.C 90,000 hours
Nominal Voltage:	230
Frequency:	50
Starting Voltage:	175
Industry:	Industrial Machines
AC Fans:	Ball Bearing Fan Metal Blade Potting
Current:	0.19
Input Power (+10% - 20%):	21
Speed:	2600
Max. Air Flow:	2.8
Max. Air Flow:	100
Max. Static Pressure:	88
Max. Static Pressure:	0.35
Noise:	46
Fan Size:	119
Fan Width:	38
Mass:	650

AC Fans