

**order part DDL-1060ZZRA5P13L0 Miniature  
Ball Bearings Metric Bearing Series**



**Metric Bearing Series**

## Detailed Specifications

|                                       |            |
|---------------------------------------|------------|
| <b>Metric:</b>                        | Shielded   |
| <b>Bore Diameter:</b>                 | 6[mm]      |
| <b>Outside Diameter:</b>              | 10[mm]     |
| <b>Width:</b>                         | 3[mm]      |
| <b>Bore Diameter:</b>                 | 0.2362[in] |
| <b>Outside Diameter:</b>              | 0.3937[in] |
| <b>Width:</b>                         | 0.1181[in] |
| <b>Fillet Radius (rsmin):</b>         | 0.1[mm]    |
| <b>Reference Diameter Inner (Li):</b> | 6.95[mm]   |
| <b>Reference Diameter Outer (Lo):</b> | 9.04[mm]   |
| <b>Ball Size (DW):</b>                | 1.191[mm]  |
| <b>Ball Complement (Z):</b>           | 9          |
| <b>Dynamic Load Rating (Cr):</b>      | 457[N]     |
| <b>Static Load Rating (Cor):</b>      | 194[N]     |
| <b>ISO/JIS Number:</b>                | 676ZZ      |
| <b>Fillet Radius (rsmin):</b>         | 0.004[in]  |
| <b>Reference Diameter Inner (Li):</b> | 0.274[in]  |
| <b>Reference Diameter Outer (Lo):</b> | 0.356[in]  |
| <b>Ball Size (DW):</b>                | 0.0469[in] |
| <b>Dynamic Load Rating Cr:</b>        | 457[N]     |
| <b>Static Load Rating Cor:</b>        | 194[N]     |