

**order part DDL-410HA5P24L0 Miniature Ball  
Bearings Metric Bearing Series**



**Metric Bearing Series**

## Detailed Specifications

|                                       |            |
|---------------------------------------|------------|
| <b>Metric:</b>                        | Open       |
| <b>Bore Diameter:</b>                 | 1[mm]      |
| <b>Outside Diameter:</b>              | 4[mm]      |
| <b>Width:</b>                         | 1.6[mm]    |
| <b>Bore Diameter:</b>                 | 0.0394[in] |
| <b>Outside Diameter:</b>              | 0.1575[in] |
| <b>Width:</b>                         | 0.063[in]  |
| <b>Fillet Radius (rsmin):</b>         | 0.1[mm]    |
| <b>Reference Diameter Inner (Li):</b> | 2.05[mm]   |
| <b>Reference Diameter Outer (Lo):</b> | 3.16[mm]   |
| <b>Ball Size (DW):</b>                | 0.794[mm]  |
| <b>Ball Complement (Z):</b>           | 6          |
| <b>Dynamic Load Rating (Cr):</b>      | 158[N]     |
| <b>Static Load Rating (Cor):</b>      | 44[N]      |
| <b>ISO/JIS Number:</b>                | 691        |
| <b>Fillet Radius (rsmin):</b>         | 0.004[in]  |
| <b>Reference Diameter Inner (Li):</b> | 0.081[in]  |
| <b>Reference Diameter Outer (Lo):</b> | 0.124[in]  |
| <b>Ball Size (DW):</b>                | 0.0313[in] |
| <b>Dynamic Load Rating Cr:</b>        | 158[N]     |
| <b>Static Load Rating Cor:</b>        | 44[N]      |