

**order part DDL-1150ZZRA5P24L0 Miniature  
Ball Bearings Metric Bearing Series**



**Metric Bearing Series**

## Detailed Specifications

|                                       |                  |
|---------------------------------------|------------------|
| <b>Metric:</b>                        | Flanged Shielded |
| <b>Bore Diameter:</b>                 | 5[mm]            |
| <b>Outside Diameter:</b>              | 11[mm]           |
| <b>Width:</b>                         | 5[mm]            |
| <b>Bore Diameter:</b>                 | 0.1969[in]       |
| <b>Outside Diameter:</b>              | 0.4331[in]       |
| <b>Width:</b>                         | 0.1969[in]       |
| <b>Flange Diameter (D1):</b>          | 12.5[mm]         |
| <b>Flange Width (C1):</b>             | 1[mm]            |
| <b>Fillet Radius (rsmin):</b>         | 0.15[mm]         |
| <b>Reference Diameter Inner (Li):</b> | 6.4[mm]          |
| <b>Reference Diameter Outer (Lo):</b> | 9.54[mm]         |
| <b>Ball Size (DW):</b>                | 1.588[mm]        |
| <b>Ball Complement (Z):</b>           | 8                |
| <b>Dynamic Load Rating (Cr):</b>      | 714[N]           |
| <b>Static Load Rating (Cor):</b>      | 276[N]           |
| <b>ISO/JIS Number:</b>                | F685ZZ           |
| <b>Flange Diameter (D1):</b>          | 0.4921[in]       |
| <b>Flange Width (C1):</b>             | 0.0394[in]       |
| <b>Fillet Radius (rsmin):</b>         | 0.006[in]        |
| <b>Reference Diameter Inner (Li):</b> | 0.252[in]        |
| <b>Reference Diameter Outer (Lo):</b> | 0.376[in]        |
| <b>Ball Size (DW):</b>                | 0.0625[in]       |
| <b>Dynamic Load Rating Cr:</b>        | 714[N]           |
| <b>Static Load Rating Cor:</b>        | 276[N]           |