

## Detailed Specifications

|                                       |            |
|---------------------------------------|------------|
| <b>Metric:</b>                        | Shielded   |
| <b>Bore Diameter:</b>                 | 4[mm]      |
| <b>Outside Diameter:</b>              | 11[mm]     |
| <b>Width:</b>                         | 4[mm]      |
| <b>Dynamic Load Rating Cr:</b>        | 714[N]     |
| <b>Static Load Rating Cor:</b>        | 276[N]     |
| <b>Bore Diameter:</b>                 | 0.1575[in] |
| <b>Outside Diameter:</b>              | 0.4331[in] |
| <b>Width:</b>                         | 0.1575[in] |
| <b>Fillet Radius (rsmin):</b>         | 0.2[mm]    |
| <b>Reference Diameter Inner (Li):</b> | 6.4[mm]    |
| <b>Reference Diameter Outer (Lo):</b> | 9.54[mm]   |
| <b>Ball Size (DW):</b>                | 1.588[mm]  |
| <b>Ball Complement (Z):</b>           | 8          |
| <b>Dynamic Load Rating (Cr):</b>      | 714[N]     |
| <b>Static Load Rating (Cor):</b>      | 276[N]     |
| <b>ISO/JIS Number:</b>                | 694ZZ      |
| <b>Fillet Radius (rsmin):</b>         | 0.008[in]  |
| <b>Reference Diameter Inner (Li):</b> | 0.252[in]  |
| <b>Reference Diameter Outer (Lo):</b> | 0.376[in]  |
| <b>Ball Size (DW):</b>                | 0.0625[in] |