

## Detailed Specifications

<b>Metric:</b>	Shielded
<b>Bore Diameter:</b>	6[mm]
<b>Outside Diameter:</b>	19[mm]
<b>Width:</b>	6[mm]
<b>Dynamic Load Rating Cr:</b>	2805[N]
<b>Static Load Rating Cor:</b>	1060[N]
<b>Bore Diameter:</b>	0.2362[in]
<b>Outside Diameter:</b>	0.748[in]
<b>Width:</b>	0.2362[in]
<b>Fillet Radius (rsmin):</b>	0.3[mm]
<b>Reference Diameter Inner (Li):</b>	8.67[mm]
<b>Reference Diameter Outer (Lo):</b>	16.26[mm]
<b>Ball Size (DW):</b>	3.969[mm]
<b>Ball Complement (Z):</b>	6
<b>Dynamic Load Rating (Cr):</b>	2805[N]
<b>Static Load Rating (Cor):</b>	1060[N]
<b>ISO/JIS Number:</b>	626ZZ
<b>Fillet Radius (rsmin):</b>	0.012[in]
<b>Reference Diameter Inner (Li):</b>	0.341[in]
<b>Reference Diameter Outer (Lo):</b>	0.64[in]
<b>Ball Size (DW):</b>	0.1563[in]