## order part DDRF-1350ZZRA3P13LY
## Miniature Ball Bearings Metric Bearing Series

## Detailed Specifications

| | |
|---|---|
| **Metric:** | Flanged Shielded |
| **Bore Diameter:** | 5[mm] |
| **Outside Diameter:** | 13[mm] |
| **Width:** | 4[mm] |
| **Bore Diameter:** | 0.1969[in] |
| **Outside Diameter:** | 0.5118[in] |
| **Width:** | 0.1575[in] |
| **Flange Diameter (D1):** | 15[mm] |
| **Flange Width (C1):** | 1[mm] |
| **Fillet Radius (rsmin):** | 0.2[mm] |
| **Reference Diameter Inner (Li):** | 6.66[mm] |
| **Reference Diameter Outer (Lo):** | 11.14[mm] |
| **Ball Size (DW):** | 2[mm] |
| **Ball Complement (Z):** | 8 |
| **Dynamic Load Rating (Cr):** | 1074[N] |
| **Static Load Rating (Cor):** | 422[N] |
| **ISO/JIS Number:** | F695ZZ |
| **Flange Diameter (D1):** | 0.5906[in] |
| **Flange Width (C1):** | 0.0394[in] |
| **Fillet Radius (rsmin):** | 0.008[in] |
| **Reference Diameter Inner (Li):** | 0.262[in] |
| **Reference Diameter Outer (Lo):** | 0.439[in] |
| **Ball Size (DW):** | 0.0787[in] |
| **Dynamic Load Rating Cr:** | 1074[N] |
| **Static Load Rating Cor:** | 422[N] |