

**order part DDRF-1350ZZRA5P24LG**  
**Miniature Ball Bearings Metric Bearing**  
**Series**



**Metric Bearing Series**

## Detailed Specifications

|                                       |                  |
|---------------------------------------|------------------|
| <b>Metric:</b>                        | Flanged Shielded |
| <b>Bore Diameter:</b>                 | 5[mm]            |
| <b>Outside Diameter:</b>              | 13[mm]           |
| <b>Width:</b>                         | 4[mm]            |
| <b>Bore Diameter:</b>                 | 0.1969[in]       |
| <b>Outside Diameter:</b>              | 0.5118[in]       |
| <b>Width:</b>                         | 0.1575[in]       |
| <b>Flange Diameter (D1):</b>          | 15[mm]           |
| <b>Flange Width (C1):</b>             | 1[mm]            |
| <b>Fillet Radius (rsmin):</b>         | 0.2[mm]          |
| <b>Reference Diameter Inner (Li):</b> | 6.66[mm]         |
| <b>Reference Diameter Outer (Lo):</b> | 11.14[mm]        |
| <b>Ball Size (DW):</b>                | 2[mm]            |
| <b>Ball Complement (Z):</b>           | 8                |
| <b>Dynamic Load Rating (Cr):</b>      | 1074[N]          |
| <b>Static Load Rating (Cor):</b>      | 422[N]           |
| <b>ISO/JIS Number:</b>                | F695ZZ           |
| <b>Flange Diameter (D1):</b>          | 0.5906[in]       |
| <b>Flange Width (C1):</b>             | 0.0394[in]       |
| <b>Fillet Radius (rsmin):</b>         | 0.008[in]        |
| <b>Reference Diameter Inner (Li):</b> | 0.262[in]        |
| <b>Reference Diameter Outer (Lo):</b> | 0.439[in]        |
| <b>Ball Size (DW):</b>                | 0.0787[in]       |
| <b>Dynamic Load Rating Cr:</b>        | 1074[N]          |
| <b>Static Load Rating Cor:</b>        | 422[N]           |