

Detailed Specifications

| | |
|---------------------------------------|------------------|
| Inch: | Flanged Shielded |
| Bore Diameter: | 4.762[mm] |
| Outside Diameter: | 12.7[mm] |
| Width: | 4.978[mm] |
| Dynamic Load Rating Cr: | 1306[N] |
| Static Load Rating Cor: | 487[N] |
| Bore Diameter: | 0.1875[in] |
| Outside Diameter: | 0.5[in] |
| Width: | 0.196[in] |
| Flange Diameter (D1): | 14.351[mm] |
| Flange Width (C1): | 1.067[mm] |
| Fillet Radius (rsmin): | 0.3[mm] |
| Reference Diameter Inner (Li): | 7[mm] |
| Reference Diameter Outer (Lo): | 11.04[mm] |
| Ball Size (DW): | 2.381[mm] |
| Ball Complement (Z): | 7 |
| Dynamic Load Rating (Cr): | 1306[N] |
| Static Load Rating (Cor): | 487[N] |
| Flange Diameter (D1): | 0.565[in] |
| Flange Width (C1): | 0.042[in] |
| Fillet Radius (rsmin): | 0.012[in] |
| Reference Diameter Inner (Li): | 0.276[in] |
| Reference Diameter Outer (Lo): | 0.435[in] |
| Ball Size (DW): | 0.0938[in] |