

## Detailed Specifications

<b>Inch:</b>	Flanged Open
<b>Bore Diameter:</b>	6.35[mm]
<b>Outside Diameter:</b>	9.525[mm]
<b>Width:</b>	3.175[mm]
<b>Dynamic Load Rating Cr:</b>	417[N]
<b>Static Load Rating Cor:</b>	205[N]
<b>Bore Diameter:</b>	0.25[in]
<b>Outside Diameter:</b>	0.375[in]
<b>Width:</b>	0.125[in]
<b>Flange Diameter (D1):</b>	10.719[mm]
<b>Flange Width (C1):</b>	0.584[mm]
<b>Fillet Radius (rsmin):</b>	0.08[mm]
<b>Reference Diameter Inner (Li):</b>	7.25[mm]
<b>Reference Diameter Outer (Lo):</b>	8.63[mm]
<b>Ball Size (DW):</b>	1[mm]
<b>Ball Complement (Z):</b>	13
<b>Dynamic Load Rating (Cr):</b>	417[N]
<b>Static Load Rating (Cor):</b>	205[N]
<b>Flange Diameter (D1):</b>	0.422[in]
<b>Flange Width (C1):</b>	0.023[in]
<b>Fillet Radius (rsmin):</b>	0.003[in]
<b>Reference Diameter Inner (Li):</b>	0.285[in]
<b>Reference Diameter Outer (Lo):</b>	0.34[in]
<b>Ball Size (DW):</b>	0.0394[in]