## order part LF-1060ZZRA5P24L0 Miniature Ball Bearings Metric Bearing Series

## Detailed Specifications

| | |
|---|---|
| **Metric:** | Flanged Shielded |
| **Bore Diameter:** | 6[mm] |
| **Outside Diameter:** | 10[mm] |
| **Width:** | 3[mm] |
| **Bore Diameter:** | 0.2362[in] |
| **Outside Diameter:** | 0.3937[in] |
| **Width:** | 0.1181[in] |
| **Flange Diameter (D1):** | 11.2[mm] |
| **Flange Width (C1):** | 0.6[mm] |
| **Fillet Radius (rsmin):** | 0.1[mm] |
| **Reference Diameter Inner (Li):** | 6.95[mm] |
| **Reference Diameter Outer (Lo):** | 9.04[mm] |
| **Ball Size (DW):** | 1.191[mm] |
| **Ball Complement (Z):** | 9 |
| **Dynamic Load Rating (Cr):** | 457[N] |
| **Static Load Rating (Cor):** | 194[N] |
| **ISO/JIS Number:** | F676ZZ |
| **Flange Diameter (D1):** | 0.4409[in] |
| **Flange Width (C1):** | 0.0236[in] |
| **Fillet Radius (rsmin):** | 0.004[in] |
| **Reference Diameter Inner (Li):** | 0.274[in] |
| **Reference Diameter Outer (Lo):** | 0.356[in] |
| **Ball Size (DW):** | 0.0469[in] |
| **Dynamic Load Rating Cr:** | 457[N] |
| **Static Load Rating Cor:** | 194[N] |