

**order part R-1980KKRA3P24LD Miniature  
Ball Bearings Metric Bearing Series**



**Metric Bearing Series**

## Detailed Specifications

|                                       |            |
|---------------------------------------|------------|
| <b>Metric:</b>                        | Shielded   |
| <b>Bore Diameter:</b>                 | 8[mm]      |
| <b>Outside Diameter:</b>              | 19[mm]     |
| <b>Width:</b>                         | 6[mm]      |
| <b>Bore Diameter:</b>                 | 0.315[in]  |
| <b>Outside Diameter:</b>              | 0.748[in]  |
| <b>Width:</b>                         | 0.2362[in] |
| <b>Fillet Radius (rsmin):</b>         | 0.3[mm]    |
| <b>Reference Diameter Inner (Li):</b> | 10.6[mm]   |
| <b>Reference Diameter Outer (Lo):</b> | 16.68[mm]  |
| <b>Ball Size (DW):</b>                | 3.175[mm]  |
| <b>Ball Complement (Z):</b>           | 8          |
| <b>Dynamic Load Rating (Cr):</b>      | 2463[N]    |
| <b>Static Load Rating (Cor):</b>      | 1059[N]    |
| <b>ISO/JIS Number:</b>                | 698ZZ      |
| <b>Fillet Radius (rsmin):</b>         | 0.012[in]  |
| <b>Reference Diameter Inner (Li):</b> | 0.417[in]  |
| <b>Reference Diameter Outer (Lo):</b> | 0.657[in]  |
| <b>Ball Size (DW):</b>                | 0.125[in]  |
| <b>Dynamic Load Rating Cr:</b>        | 2463[N]    |
| <b>Static Load Rating Cor:</b>        | 1059[N]    |