

Miniature Bearings Metric



Metric

Detailed Specifications

Metric

| | |
|---------------------------------------|------------------|
| Metric: | Flanged Shielded |
| Bore Diameter: | 5 |
| Outside Diameter: | 13 |
| Width: | 4 |
| Dynamic Load Rating Cr: | 1074 |
| Static Load Rating Cor: | 422 |
| Bore Diameter: | 0.1969 |
| Outside Diameter: | 0.5118 |
| Width: | 0.1575 |
| Flange Diameter (D1): | 15 |
| Flange Width (C1): | 1 |
| Fillet Radius (rsmin): | 0.2 |
| Reference Diameter Inner (Li): | 6.66 |
| Reference Diameter Outer (Lo): | 11.14 |
| Ball Size (DW): | 2 |
| Ball Complement (Z): | 8 |
| Dynamic Load Rating (Cr): | 1074 |
| Static Load Rating (Cor): | 422 |
| ISO/JIS Number: | F695ZZ |
| Flange Diameter (D1): | 0.5906 |
| Flange Width (C1): | 0.0394 |
| Fillet Radius (rsmin): | 0.008 |
| Reference Diameter Inner (Li): | 0.262 |
| Reference Diameter Outer (Lo): | 0.439 |
| Ball Size (DW): | 0.0787 |