order part RF-1950ZZRA5P24LY Miniature Ball Bearings Metric Bearing Series

Detailed Specifications

Metric:	Flanged Shielded
Bore Diameter:	5[mm]
Outside Diameter:	19[mm]
Width:	6[mm]
Bore Diameter:	0.1969[in]
Outside Diameter:	0.748[in]
Width:	0.2362[in]
Flange Diameter (D1):	22[mm]
Flange Width (C1):	1.5[mm]
Fillet Radius (rsmin):	0.3[mm]
Reference Diameter Inner (Li):	8.67[mm]
Reference Diameter Outer (Lo):	16.26[mm]
Ball Size (DW):	3.969[mm]
Ball Complement (Z):	6
Dynamic Load Rating (Cr):	2805[N]
Static Load Rating (Cor):	1060[N]
ISO/JIS Number:	F635ZZ
Flange Diameter (D1):	0.8661[in]
Flange Width (C1):	0.0591[in]
Fillet Radius (rsmin):	0.012[in]
Reference Diameter Inner (Li):	0.341[in]
Reference Diameter Outer (Lo):	0.64[in]
Ball Size (DW):	0.1563[in]
Dynamic Load Rating Cr:	2805[N]
Static Load Rating Cor:	1060[N]