## order part RF-620ZZRA1P58LY Miniature Ball Bearings Metric Bearing Series

Metric Bearing Series

## Detailed Specifications

| | |
|---|---|
| **Metric:** | Flanged Shielded |
| **Bore Diameter:** | 2[mm] |
| **Outside Diameter:** | 6[mm] |
| **Width:** | 3[mm] |
| **Bore Diameter:** | 0.0787[in] |
| **Outside Diameter:** | 0.2362[in] |
| **Width:** | 0.1181[in] |
| **Flange Diameter (D1):** | 7.5[mm] |
| **Flange Width (C1):** | 0.8[mm] |
| **Fillet Radius (rsmin):** | 0.15[mm] |
| **Reference Diameter Inner (Li):** | 3.1[mm] |
| **Reference Diameter Outer (Lo):** | 5.23[mm] |
| **Ball Size (DW):** | 1.191[mm] |
| **Ball Complement (Z):** | 6 |
| **Dynamic Load Rating (Cr):** | 330[N] |
| **Static Load Rating (Cor):** | 99[N] |
| **ISO/JIS Number:** | F692ZZ |
| **Flange Diameter (D1):** | 0.2953[in] |
| **Flange Width (C1):** | 0.0315[in] |
| **Fillet Radius (rsmin):** | 0.006[in] |
| **Reference Diameter Inner (Li):** | 0.122[in] |
| **Reference Diameter Outer (Lo):** | 0.206[in] |
| **Ball Size (DW):** | 0.0469[in] |
| **Dynamic Load Rating Cr:** | 330[N] |
| **Static Load Rating Cor:** | 99[N] |