## order part RF-725ZZRA1P25L0 Miniature Ball Bearings Metric Bearing Series

## Detailed Specifications

| | |
|---|---|
| **Metric:** | Flanged Shielded |
| **Bore Diameter:** | 2.5[mm] |
| **Outside Diameter:** | 7[mm] |
| **Width:** | 3.5[mm] |
| **Bore Diameter:** | 0.0984[in] |
| **Outside Diameter:** | 0.2756[in] |
| **Width:** | 0.1378[in] |
| **Flange Diameter (D1):** | 8.5[mm] |
| **Flange Width (C1):** | 0.9[mm] |
| **Fillet Radius (rsmin):** | 0.15[mm] |
| **Reference Diameter Inner (Li):** | 3.8[mm] |
| **Reference Diameter Outer (Lo):** | 5.93[mm] |
| **Ball Size (DW):** | 1.191[mm] |
| **Ball Complement (Z):** | 7 |
| **Dynamic Load Rating (Cr):** | 380[N] |
| **Static Load Rating (Cor):** | 126[N] |
| **ISO/JIS Number:** | F69/2.5ZZ |
| **Flange Diameter (D1):** | 0.3346[in] |
| **Flange Width (C1):** | 0.0354[in] |
| **Fillet Radius (rsmin):** | 0.006[in] |
| **Reference Diameter Inner (Li):** | 0.15[in] |
| **Reference Diameter Outer (Lo):** | 0.234[in] |
| **Ball Size (DW):** | 0.0469[in] |
| **Dynamic Load Rating Cr:** | 380[N] |
| **Static Load Rating Cor:** | 126[N] |