## order part RIF-5632RA5P13LY Miniature Ball Bearings Inch Series Bearings

## Detailed Specifications

| | |
|---|---|
| **Inch:** | Flanged Open |
| **Bore Diameter:** | 4.763[mm] |
| **Outside Diameter:** | 7.938[mm] |
| **Width:** | 2.779[mm] |
| **Bore Diameter:** | 0.1875[in] |
| **Outside Diameter:** | 0.3125[in] |
| **Width:** | 0.1094[in] |
| **Flange Diameter (D1):** | 9.119[mm] |
| **Flange Width (C1):** | 0.584[mm] |
| **Fillet Radius (rsmin):** | 0.080[mm] |
| **Reference Diameter Inner (Li):** | 5.620[mm] |
| **Reference Diameter Outer (Lo):** | 7.080[mm] |
| **Ball Size (DW):** | 1.191[mm] |
| **Ball Complement (Z):** | 7.000 |
| **Dynamic Load Rating (Cr):** | 391.000[N] |
| **Static Load Rating (Cor):** | 142.000[N] |
| **Flange Diameter (D1):** | 0.3590[in] |
| **Flange Width (C1):** | 0.0230[in] |
| **Fillet Radius (rsmin):** | 0.003[in] |
| **Reference Diameter Inner (Li):** | 0.221[in] |
| **Reference Diameter Outer (Lo):** | 0.279[in] |
| **Ball Size (DW):** | 0.0469[in] |
| **Dynamic Load Rating Cr:** | 391[N] |
| **Static Load Rating Cor:** | 142[N] |